


CUSTOMER OUTLINE DRAWING

REVISONS			
REV	DESCRIPTION	DATE	APPR
1	Initial Release	21-Oct-20	S.X



NOTES:

- Material
 - 1-1 Plunger: Copper Alloy,
 - 1-2 Body: Copper Alloy.
 - 1-3 Spring: stainless steel
- Finish
 - 2-1 Plunger:1u" Min. Gold over 50u" Min. Nickel
 - 2-2 Body:1u" Min. Gold over 50u" Min. Nickel
- Mechanical Specification
 - 3-1 Spring Force:60±10gf at 3.0mm Working height
 - 3-2 Durability:10,000 cycles
- Electrical Specifications
 - 4-1 Rating Voltage:24V
 - 4-2 Rating Current: 1A max.
 - 4-3 Contact Resistance: 100 mohms max.at working height
- Environmental Performance
 - 5-1 Storage and operating temperature range:-40°C~+85°C
 - 5-2 Humidity: 10% RH to 90% RH.
 - 5-3 Salt Spray: 24H min.
 - 5-4 RoHS Compliant.
- Package: PE Bag

UNLESS OTHERWISE SPECIFIED,TOLERANCE ARE:
X,±0.5 .X±0.1 .XX±0.05 .XXX±0.005 ANGEL±2

NOTICE- These drawing,specifications,or other date are,and remain property of wizconn corporation.(2)are confidential and not to be disclosed to any person other than those to whom they are given by wizconn corporation,or to any other person to anyone for any purpose is not to be regarded by implication orotherwise in any manner liscensing, granting rights to permitting such holder or any others person to manufacture,use or sell any product,process or design, patented or otherwise,that may in any way be related to or disclosed by said drawings,specifications,or other date.

TITLE:

POGO PIN
(ø1.5*4.0)



深圳市为致康科技有限公司

Shenzhen Wizconn Technology Ltd.

USE ON: CUSTOMER	DESIGN: Jason	DWG NO.: FP154035-1-PB		
MATERIAL:	CHECK: Jason	PART NO.: FP154035-1-PB		
FINISH:	APPROVED: Cliff	SCALE: 1:1	REV: 1	SHEET: 1 OF 1
THIRD ANGLE PROJECTION		UNIT: mm	CAD FILE:	